Residential/Commercial

# PRO-SPRAY®

### RESIDENTIAL OR COMMERCIAL, THIS VERSATILE SPRINKLER IS THE CONTRACTOR'S CHOICE.

#### **FEATURES**

- Application: Residential/commercial
- Models: Shrub, 2", 3", 4", 6", 12"
- No side inlet (NSI) version available in 6" and 12"
- Warranty period: 5 years

#### ADVANCED FEATURES

- .. Co-molded wiper seal with UV resistant material
- •• Body cap won't leak under high pressure
- · Drain check valve (optional)
- = Detailed description on pages 32 and 33

#### **OPERATING SPECIFICATIONS**

Recommended pressure range: 15 to 70 PSI

#### **FACTORY INSTALLED OPTIONS**

Drain check valve (up to 10' of elevation)

Reclaimed water ID cap


#### **USER INSTALLED OPTIONS**

Drain check valve (up to 10' of elevation; P/N 437400)

Reclaimed water ID cap (P/N 458520)

Snap-on reclaimed cover (P/N PROSRCCAP)

- Heavy-duty retraction spring
- Innovative directional flush plug design
- Reclaimed purple body cap (optional)
- Compatible with all female threaded nozzles





PROS-00:

Inlet size: 1/2" Female NPT



PROS-03: Overall height: 5" Exposed diameter: 21/4" Inlet size: 1/2" Female NPT

PROS-04: Overall height: 5%\* Exposed diameter: 21/4" Inlet size: 1/2" Female NPT



MP ROTATOR



PRO-SPRAY FIXED PRO ADJUSTABLE



ARC NOZZLES

## WORKS BEST WITH

SPECIFICATIONBUILDER www.hunterindustries.com/PROSPRAY

STANDARD MODELS	OPTIONS
PROS-00 = Shrub adapter	(blank) = No option  CV = Factory-installed drain check valve (pop-up models only)  CV-R = Factory-installed reclaimed body cap (shrub molded in purple)  6" and 12" models ordered as CV will come as no side inlet
PROS-02 = 2* pop-up	
PROS-03 = 3* pop-up	
PROS-04 = 4" pop-up	
PROS-06 = 6* pop-up	
PROS-06-NSI = 6* pop-up with no side inlet	
PROS-12 = 12* pop-up	
PROS-12-NSI = 12" pop-up with no side inlet	

**EXAMPLES** 

PROS-04 - 10A	4* pop-up, and 10' adjustable nozzle
PROS-06 - CV - 12H	6" pop-up, drain check valve, and 12" half circle nozzle
PROS-12 - CV-R - RCS	12" pop-up, drain check valve, reclaimed body cap, and right corner strip

