

ROAM

APPLICATION

Residential/Light Commercial

RANGE

1000'

www.hunterindustries.com/ROAM

THE ROAM REMOTE ALLOWS FOR CONTROLLER OPERATION UP TO 1000 FEET.

FEATURES

- Designed to work with Hunter ACC, I-Core, ICC, Pro-C, PCC, and X-Core controllers through a SmartPort® connection
- 128 programmable addresses for use of multiple ROAM remotes in the same neighborhood
- Variable run times to adjust run time without modifying regular program
- Maximum stations supported: 240
- Run times: 1 to 90 minutes
- Range: Up to 1000 ft (line of sight)
- Transmitter power source: 4 AAA batteries (included)
- Receiver power source: 24 VAC, 10 mA (provided by controller)
- System operating frequency: 433 MHz
- FCC approved



Transmitter and receiver:
7" H x 2¼" W x 1¼" D

SmartPort®

ROAM and ICR remote controls require the installation of a SmartPort wiring harness. This consists of a connector that is wired to the SmartPort terminal on the controller and will accept either the ROAM or ICR remote receiver.



SPECIFICATIONBUILDER

MODELS

ROAM-KIT – Transmitter, receiver (SmartPort® wiring harness, and 4 AAA batteries included)

ROAM-TR – Transmitter (4 AAA batteries included)

ROAM-R – Receiver

ROAM-WH – SmartPort wiring harness (length: 6 ft)

SRR-SCWH – Shielded SmartPort wiring harness (length: 25 ft)

EXAMPLES

ROAM-KIT

ROAM-R

ICR

APPLICATION

Commercial

RANGE

2 Miles

www.hunterindustries.com/ICR

REMOTELY ACCESS CONTROLLERS UP TO TWO MILES AWAY.

FEATURES

- Up to 2 mile range for remote manual operation of Hunter irrigation systems
- Designed to work with Hunter ACC, I-Core, ICC, Pro-C, PCC, and X-Core controllers through a SmartPort® connection
- 128 different programmable addresses
- Variable run times to change run time without modifying regular program
- Display shows remaining battery life
- Maximum stations supported: 240
- Run times: 1 to 90 minutes
- Large LCD display, push-button operation
- Transmitter power source: 4 AA alkaline batteries (included)
- Receiver power source: 24 VAC, from controller through a SmartPort® connector
- System operating frequency: 27 MHz band
- SmartPort can be mounted up to 50' from controller (use SRR-SCWH shielded cable wiring harness)
- FCC approved: No FCC license required
- Rugged plastic carrying case included



Transmitter (no antenna):
6½" H x 3¼" W x 1¼" D
Receiver (no antenna):
6¼" H x 3" W x 1¼" D

SPECIFICATIONBUILDER

MODELS

ICR-KIT – Transmitter, receiver SmartPort® wiring harness, and carrying case

ICR-TR – Handheld transmitter (4 AA batteries included)

ICR-R – Receiver unit (SmartPort wiring harness included)

ICR-CASE – Plastic carrying case

ROAM-WH – SmartPort wiring harness (length: 6 ft/1.8 m)

SRR-SCWH – Shielded SmartPort wiring harness (length: 25 ft)

OPTIONS

(blank) – No option
A – Australia and other international markets

EXAMPLES

ICR-KIT